

47KE

Key-In-Lever Entrance

Function:

- 08 - Entrance by trim (key locks or unlocks trim)

Certifications:

- Meets ANSI/BHMA A156.3-2014 Grade 1
- Complies with ANSI A117.1 for accessible buildings and facilities (Levers only)



PRODUCT SPECIFICATIONS

LEVER OPTIONS:

- Archer, August, Withnell levers
- Apollo knob

PROJECTION:

- 3-1/16" (78 mm) for Archer, 3-3/16" (80 mm) for August, 3-1/16" (78 mm) for Withnell
- 3-1/8" (79 mm) for Apollo

STANDARD DOOR PREP:

- 2-1/8" (54 mm) diameter (cross bore)
- Turtle Prep compatible ANSI A156.115

ROSE DIAMETER:

- 3-3/8" (86 mm)

DOOR THICKNESS:

- 1-3/4" (45mm)

KEYS:

- Two (2) brass keys per lock

CYLINDERS:

- Conventional cylinder, C keyway - standard on levers and knob
- Small Format Interchangeable Core housing available on levers only (cylinder sold separately, 3981)
- Other keying options available from factory

BACKSET:

- 2-3/4" (70 mm) - standard frame and door (161 or Turtle Prep)
- Exit device dependent

FINISHES:

- ALM, DBZ, US3, US32D for levers
- US32D for knob

NOTES:

- 4700 trim have steel bodies and zinc handles. The exception being US32D which is stainless steel.

WARRANTY:

- Five-years